

**GLOWING EFFECT**

Instant on to full brightness and luminance uniformity.

**POLLUTION FREE**

RoHS compliant and are 100% mercury free.

**COLOR SELECT TECHNOLOGY**

Adjustable: 2700&5000K

Adjustable: 2700&3000&3500&4000&5000K

**DIMMABLE**

TRIAC Dimming.



Introduce :

Enjoy all the benefits of advanced LED energy-saving technology with the TOPSTAR LED Light Bulb. This LED bulb replaces incandescent bulb, producing a similar light output using less electricity. Preset the color temperature with a toggle on the bulb for your need. Combining innovative LED technology with filament strips, the bulbs provide the benefits of LEDs with the look of a decorative bulb. Get instant on to full brightness with relatively cool running performance. These TOPSTAR bulbs have an average life of 15,000 hours are RoHS compliant, and are 100% mercury free. Choose a bulb for general purpose residential or commercial applications.

Features & Benefits :

- Instant on to full brightness and TRIAC dimming.
- These LED lights do not contain mercury and won't release any hazardous gases into the air.
- 2 or 5 color temperatures optional, let you choose your favorite color temperature.
- With a lifetime of up to 15,000 hours, you can reduce the hassle of frequently replacing your light bulbs.
- Energy efficient LED technology uses considerably less power and last longer compared to equivalent incandescent lights.

Application place :

The product is suitable for ceiling fixture, table lamp and so on.

Technical Date :

	TSZ5.5B11-LD00*	TSZ5.5A15-LD00*	TSZ8G25-LD00*	TSZ8ST19-LD00*
Lamp Type	B11	A15	G25	ST19
Rated Voltage	120V	120V	120V	120V
Rated Power	5.5W	5.5W	8W	8W
Incandescent Equivalent	60W	60W	60W	60W
Power Factor	0.7	0.7	0.7	0.7
Declared Luminous Flux	500lm	500lm	800lm	800lm
Color Temperature	2700K&5000K		2700&3000&3500&4000&5000K	
Average Ra	90		80	
Beam Angle	290°			
Average Life	15000H			
Working Temperature	-20°C(-4°F)~40°C(+104°F)			
Material	Glass			
Dimmable	Yes			

Diameter	1.38Inch (35mm)	1.97Inch (50mm)	3.15Inch (80mm)	2.28Inch (58mm)
Height	4.68Inch (102mm)	3.62Inch (92mm)	4.91Inch (125mm)	5.46Inch (139mm)
Weight	0.055Lb (25g)	0.055Lb (25g)	0.11Lb (50g)	0.099Lb (45g)
Base	E12/E26	E12/E26	E26	E26
Environment	Damp Location	Damp Location	Damp Location	Damp Location
Certificate	ETL、FCC、CEC-T20	ETL、FCC、CEC-T20	ETL、FCC	ETL、FCC