

Zed Tri-proof Light B Type











TOPSTAR — Since 1958 —

Zed Tri-proof Light B Type

Application:

LED integrated waterproof fixture in 600mm, 1200mm, 1500mm nominal length . High efficiency, up to 135lm/W system efficiency and 45,000 hours lifetime. Supplied with movable stainless steel mounting clips for a flexible and easy installation. LED Zed Tri-proof luminaires that provide an ideal solution for applications such as workshops, garages and outdoor covered spaces.


Features & Benefits:

- Easy Installation by mounting brackets.
- High quality robust PC UV Resistant Material.
- IP65、IK08.
- Function optional: Standard/Microwave/EmergencyEmergency power than standard 3W, emergency state can be used for 3 hours, light pass 200lm.
- Microwave and emergency voltage 220~240V.

Application place:

Car parks/ Underground Areas/Warehouses/Workshops.

Available Sizes:



| Туре | Height | Width | Length |
|--------------------------|--------|-------|--------|
| Zed Tri-proof B Type 2Ft | 72mm | 83mm | 600mm |
| Zed Tri-proof B Type 4Ft | 72mm | 83mm | 1200mm |
| Zed Tri-proof B Type 5Ft | 72mm | 83mm | 1500mm |



Zed Tri-proof Light B Type

Technical Date:

| Lamp Type | Zed Tri-proof B Type 2Ft Zed Tri-proof | | f B Type 4Ft | Zed Tri-proof B Type 5Ft | | | | |
|------------------------|--|--------|--------------|--------------------------|--------|--------|--|--|
| Rated Voltage | 220-240V | | | | | | | |
| Rated Power | 10W | 20W | 20W | 40W | 30W | 50W | | |
| Displacement FactorDF | DF0.7 | | | DF0.9 | | | | |
| Declared Luminous Flux | 1300lm | 2600lm | 2700lm | 5400lm | 4050lm | 6750lm | | |
| Color Temperature | 3000K/4000K/6500K | | | | | | | |
| Average Ra | Ra80 | | | | | | | |
| Beam Angle | 120° | | | | | | | |
| Average Life | 45000H | | | | | | | |
| Working Temperature | -10~40°C | | | | | | | |
| Material | Resistant UV PC Material | | | | | | | |
| Dimmable | NO | | | | | | | |
| Environment | IP65 | | | | | | | |
| Certificate | CE/CB/ERP | | | | | | | |