

TOPSTAR

— Since 1958 —

Commercial EV Charger



Bluetooth



Wi-Fi



OCPP 1.6J



RFID

Suitable for NA



Features

- OTA Remote Firmware Updates
- OCPP 1.6J Fully Compliance
- Enclosure Rating: NEMA Enclosure Type 4

Application:

- Commercial Area
- Public Parking Garage
- Residential Area

Technical Data:

	32A Max	40A Max	48A Max
Electrical Parameter	Single phase input: 208-240VAC 60 Hz		
	7.6kW at 240 VAC	9.6kW at 240 VAC	11.5kW at 240 VAC
	Input Cord Hardwired		
Output Cable & Connector	18 FT/5.5 m cable (25 FT/7.5m optional)		
	SAE J1772, NACS standard compliance		
Environmental Parameter	NEMA Enclosure Type4: Weatherproof, dust-tight		
	IK10: Resistant polycarbonate case		
	Operating Temperature: -22°F to 122°F (-30°C to 50°C)		
Dimension	Main enclosure:12.3in × 10.2in × 4.1in (313mm × 260mm × 105mm)		
Standards	NEC625, UL2594, UL 2231, OCPP 1.6J compliance		
Certification	ETL, FCC, Energy Star Listed		

Optional

- 4G Module
- Color customization
- Power balance EMS