



Emergency Battery

Built-in high quality 1500mAh lithium emergency battery.



Emergency Lighting Times

Get up to 5 hours of emergency battery backup lighting.



On-off Keying

Use the light like a flashlight by just pressing the power button ON/OFF.



Introduce :

Get up to 5 hours of emergency battery backup lighting if you lose power with the TOPSTAR Backup Battery LED Bulb. Reliable, rechargeable emergency lighting, this bulb turns on even during blackouts. Install Battery Backup Light Bulbs and make frantic situations less frantic. They're perfect for locations that have frequent storms or power surges. No more hunting in the dark for flashlights and candles. A21 shape backup bulbs fit in a standard E26 light bulb fixture and work just like a regular bulb until the power goes out. When the power cuts out, push the power button to switch to battery power and they'll continue to shine. The bulbs use just 8 watts while providing a similar 760-lumen light compared to 60-watt incandescent bulbs. Save 85% on energy costs with the same Soft White 2700K or Daylight 5000K glow. They charge while being used as a regular bulb, so they'll be ready to shine the power goes out.

Features & Benefits :

- Charges while in use as a regular bulb so it will have full power during outages.
- Built-in high quality 1500mAh lithium emergency battery.
- Press the button when the power goes out for up to 5 hours of emergency light.
- Energy efficient LED technology uses considerably less power and last longer compared to equivalent incandescent lights.

Application place :

The product is suitable for residential home, living room and so on.

Technical Date :

	TSZ8A21-L
Lamp Type	A21
Rated Voltage	120V
Rated Power	8W
Incandescent Equivalent	60W
Power Factor	0.5
Declared Luminous Flux	760lm
Battery Style Lumens	90lm
Color Temperature	3000K
Average Ra	80
Beam Angle	180°
Average Life	15000H
Battery Capacity	1500mAh
Working Temperature	-20°C(-4°F)~40°C(+104°F)

Material	Plastic
Dimmable	NO
Diameter	2.60Inch(66mm)
Height	5.59Inch(142mm)
Weight	0.287Lb(130g)
Base	E26
Environment	Damp Location
Certificate	ETL、FCC