

A Lamp - 3Way





A Lamp - 3Way

 $(-\tilde{A}_{\rm s})$

GLOWING EFFECT Instant on to full brightness and luminance uniformity



POLLUTION FREE RoHS compliant and are 100% mercury free



POWER SELECT TECHNOLOGY 3 options power outputs option.





Introduce:

Enjoy all the benefits of advanced LED energy-saving technology with the TOPSTAR 3-Way A19 LED Light Bulb. This non-dimmable 5000K Daylight light bulb emits a cool, crisp white light ideal for closets, offices, and kitchens. It can be used in 3-way lamps and fixtures to cycle through 3 different brightness settings equivalent to max 150-watt incandescent bulbs. Use the lower setting for unwinding, then increase the brightness for reading, working on tasks, and seeing objects in finer detail. Save time and money with LED light bulbs that last years and use just a fraction of the energy of an incandescent bulb. Each bulb has an average life of 10,000 hours, is RoHS compliant, and is 100% mercury free. Choose the bulb from TOPSTAR for your general-purpose lighting needs.

Features & Benefits:

- Instant on to full brightness
- Compatible with 3-way light fixtures
- These LED lights do not contain mercury and won't release any hazardous gases into the air
- With a lifetime of up to 10,000 hours, you can reduce the hassle of frequently replacing your light bulbs
- Energy efficient LED technology uses considerably less power and last longer compared to equivalent incandescent lights

Application place:

The product is suitable for residential home, living room and so on.

Available Sizes:

Diameter				
<				
-	A	Туре	Diameter	Height
		TSG3&9&13A19-L	2.35 Inch(60mm)	4.57 Inch(116mm)
	Height	TSG6&12&17A19-L	2.35 Inch(60mm)	4.57 Inch(116mm)
1	¥			



Technical Date:

	TSG3&9&13A19-L	TSG6&12&17A19-L	
Lamp Type	A19		
Rated Voltage	120V		
Rated Power	3&9&13W	6&12&17W	
Incandescent Equivalent	30&70&100W	50&100&150W	
Power Factor	0.7		
Declared Luminous Flux	305&995&1300lm	615&1540&2155lm	
Color Temperature	2700K/5000K		
Average Ra	Ra80		
Beam Angle	220°		
Average Life	10000H		
Working Temperature	-10°(14°F)~40°C(+104°F)		
Material	Plastic		
Dimmable	NO		
Weight	0.265Lb(120g)		
Base	E26d		
Environment	Damp Location		
Certificate	ETL, FCC		