



## Features

- Charge cable is self-retracting and locking
- Cable length about 18-feet (or 25-feet) with Type 1 SAE J1772 connector
- Universal mounting bracket for pedestal, wall or ceiling placement
- Suitable for indoor and outdoor use

**Suitable for NA & EU**

Technical Data:

|                              |   |
|------------------------------|---|
| Material                     | PA6 nylon reinforced 30%,304 stainless steel standard screws,<br>hot rolled thin steel plate bracke |
| Dimension                    | 13.5in × 11.8in × 7.2in (410mm × 360mm × 220mm)   |
| Weight                       | 25.3Bs/11.5kg (Excluded cable)  |
| Cable Winding Length         | Based on the length of the charging cable   |
| Pulling and Rolling Strength | ≥2.2LBs   |
| Operating Temperature        | -22°F to 122°F (-30°C to 50°C )   |
| Life Span                    | ≥10000times(Slow pull natural recovery)   |
| Safety                       | Flame-retardant nylon PA66 flame-retardant reinforced 30% nylon fire-resistant material.            |
| Output Cable                 | Connects to existing EVSE. Type 1 SAE J1772 cord, AC Level 2, 32-48A rated (7.6-11.5 kW)            |
|                              | Cable Management System is only available in 7FT pedestal.  |