

**TOPSTAR**

— Since 1958 —

# LCD Commercial EV Charger



Bluetooth



Wi-Fi



OCPP 1.6J



RFID

**Suitable for NA**



## Features

- OTA Remote Firmware Updates
- 4.3" LCD Screen
- OCPP 1.6J Fully Compliance
- Enclosure Rating: NEMA Enclosure Type 4

## Application:

- Commercial Area
- Public Parking Garage
- Residential Area

## Technical Data:

	32A Max	40A Max	48A Max
<b>Electrical Parameter</b>	Single phase input: 208-240VAC 60 Hz		
	7.6kW at 240 VAC	9.6kW at 240 VAC	11.5kW at 240 VAC
	Hardwired		
<b>Input Cord</b>	Hardwired		
<b>Output Cable &amp; Connector</b>	18 FT/5.5 m cable (25 FT/7.5m optional)		
	SAE J1772, NACS standard compliance		
<b>Environmental Parameter</b>	NEMA Enclosure Type4: Weatherproof, dust-tight		
	IK08: Resistant polycarbonate case		
	Operating Temperature: -22°F to 122°F (-30°C to 50°C )		
<b>Dimension</b>	Main Enclosure: 9.7in x 12.8in x 3.8in (247mm x 326mm x 97mm)		
<b>Standards</b>	NEC625, UL2231, UL2594, OCPP1.6J, ISO15118, CTEP compliance		
<b>Certification</b>	ETL, FCC, Energy Star compliance		

## Optional

- 4G Module
- Power balance EMS
- Color customization