



TRIAC Dimming



5CCT Selectable



Night light



Application :

Select from Topstar's recessed downlight LED luminaires include modules/trim, ultra-slim, surface mount, LED downlights with junction box, commercial downlight, and night-light. Our luminaires are perfect choice for your new or remodel construction project with their lower energy and maintenance cost. We have products for various application, such as residential application, like living room and kitchen, and commercial application, such as school and corporate office space. Our downlight LED luminaires comes in different option, such as CCT and/or wattage selectable, standard style, 277- 347V option, and many more. Many of Topstar's downlight LED luminaires are certify for ETL, FCC, Energy Star, CA T20, T24 and CEC.

Features :

- 5 CCT selectable.
- TRIAC dimming.
- Compatible with most of dimmers.
- Quick and easy installation.

Application place :

The product is suitable for Living room, Bedroom, Apartments, Hotel, Restaurant and so on.

Technical Date :

Picture				
	LED Disk Light		LED Disk light with night light	
Type	LED Disk Light		LED Disk light with night light	
Rated Voltage	120V	120V	120V	120V
Size	4inch	6inch	4inch	6inch
Function	Basic	Basic	Night Light	Night Light
Rated Power	10W	15W	10W	15W
Power Factor	0.7	0.7	0.7	0.7
Declared Luminous Flux	650lm	1000lm	650lm	1000lm
Color Temperature	5CCT(27000K/3000K/3500K/4000K/5000K)	5CCT(27000K/3000K/3500K/4000K/5000K)	5CCT(27000K/3000K/3500K/4000K/5000K)	5CCT(27000K/3000K/3500K/4000K/5000K)
Average Ra	90	90	90	90
Beam Angle	110°	110°	110°	110°
Average Life	35000H	35000H	35000H	35000H
Working Temperature	-20°C(-4°F)~40°C(+104°F)	-20°C(-4°F)~40°C(+104°F)	-20°C(-4°F)~40°C(+104°F)	-20°C(-4°F)~40°C(+104°F)

Material	Metal+ PC	Metal+ PC	Metal+ PC	Metal+ PC
Dimmable	TRIAC	TRIAC	TRIAC	TRIAC
Night light	No	No	YES	YES
Length	5.91Inch(150mm)	7.09Inch(180mm)	5.91Inch(150mm)	7.09Inch(180mm)
Width	5.91Inch(150mm)	7.09Inch(180mm)	5.91Inch(150mm)	7.09Inch(180mm)
Height	1.18Inch(30mm)	1.4Inch(35.6mm)	1.18Inch(30mm)	1.4Inch(35.6mm)
Environment	Damp Location	Damp Location	Damp Location	Damp Location
Certificate	ETL、FCC、T24	ETL、FCC、T24	ETL、FCC、T24	ETL、FCC、T24