


A-Type Filament - CCT







GLOWING EFFECT

Instant on to full brightness and luminance uniformity.



POLLUTION FREE

RoHS compliant and are 100% mercury free.



COLOR SELECT TECHNOLOGY

Adjustable: 2700&3000&3500&4000&5000K



DIMMABLE

TRIAC Dimming.







Introduce:

Enjoy all the benefits of advanced LED energy-saving technology with the TOPSTAR LED Light Bulb. This LED bulb replaces incandescent bulb, producing a similar light output using less electricity. Preset the color temperature with a toggle on the bulb for your need. Combining innovative LED technology with filament strips, the bulbs provide the benefits of LEDs with the look of a traditional bulb. Get instant on to full brightness with relatively cool running performance. These TOPSTAR bulbs have an average life of 15,000 hours are RoHS compliant, and are 100% mercury free. Choose a bulb for general purpose residential or commercial applications.

Features & Benefits:

- Instant on to full brightness and TRIAC dimming.
- These LED lights do not contain mercury and won't release any hazardous gases into the air.
- 5 color temperatures optional, let you choose your favorite color temperature.
- With a lifetime of up to 15,000 hours, you can reduce the hassle of frequently replacing your light bulbs.
- Energy efficient LED technology uses considerably less power and last longer compared to equivalent incandescent lights.

Application place:

The product is suitable for ceiling fixture, table lamp and so on.

Technical Date:

	TSZ8A19-LD00*	TSZ13A19-LD00*
Lamp Type	A19	A19
Rated Voltage	120V	120V
Rated Power	8W	13W
Incandescent Equivalent	60W	100W
Power Factor	0.7	0.7
Declared Luminous Flux	800lm	1520lm
Color Temperature	2700&3000&3500&4000&5000K	
Average Ra	80	80
Beam Angle	290°	290°
Average Life	15000H	15000H
Working Temperature	-20°C(-4°F)~40°C(+104°F)	-20°C(-4°F)~40°C(+104°F)
Material	Glass	Glass
Dimmable	Yes	Yes



A-Type Filament - CCT

Diameter	2.36Inch(60mm)	2.36Inch(60mm)
Height	4.56Inch(116mm)	4.56Inch(116mm)
Weight	0.099Lb(45g)	0.099Lb(45g)
Base	E26	E26
Environment	Damp Location	Damp Location
Certificate	ETL\ FCC	ETL\ FCC