



Ceiling Fixture
Double Ring



Silver Ceiling Fixture
Modern Simple Style



Ceiling Fixture
Skydome




Ceiling Fixture
Simple Circle Hollow



TRIAC Dimming



5CCT Selectable



High quality metal shell



Night light



Application :

An LED ceiling fixture is one of the easiest ways to bring quality light into any rooms. These versatile modern fixtures are highly adaptable to a variety of spaces, making them a favorite among end-users and DIY alike. Today's flush ceiling fixtures have come a long way from the basic, builder-grade globes of the past. Designed as a flexible lighting solution for both retrofit and new construction. LED ceiling fixtures are available in a range of shape, sizes, and color temperatures. They can be installed in many places throughout the house, with the most popular being closets, hallways, foyers, spare bedrooms, and laundry and mud rooms. LED ceiling flush mounts and semi-flush mounts are ideal for adding style to a standard height space without sacrificing usability.



Features & Benefits :

- 5 CCT selectable
- TRIAC dimming.
- Compatible with most of dimmers.
- Brushed nickel/aluminium finish with durable frame.
- Quick and easy installation.

Application place :

The product is suitable for Bathroom, Hallways, Restaurants, Hotel and so on.

Technical Data :

Picture				
Type	LED Surface Mount Ceiling Fixture Double Ring	LED Surface Mount Silver Ceiling Fixture Modern Simple Style	LED Surface Mount Ceiling Fixture Skydome	LED Surface Mount Ceiling Fixture Simple Circle Hollow
Rated Voltage	120V	120V	120V	120V
Rated Power	15W	20W	20W	20W
Power Factor	0.7	0.7	0.7	0.7
Declared Luminous Flux	1200lm	1200lm	1200lm	1200lm
Color Temperature	5CCT(27000K/3000K/3500K/4000K/5000K)	5CCT(27000K/3000K/3500K/4000K/5000K)	5CCT(27000K/3000K/3500K/4000K/5000K)	5CCT(27000K/3000K/3500K/4000K/5000K)
Average Ra	80	80	80	80
Beam Angle	120°	120°	120°	120°
Average Life	15000H	15000H	15000H	15000H

Working Temperature	-20°C(-4°F)~ 40°C(+104°F)	-20°C(-4°F)~ 40°C(+104°F)	-20°C(-4°F)~ 40°C(+104°F)	-20°C(-4°F)~ 40°C(+104°F)
Material	Metal+ PS	Metal+ PS	Metal+ PS	Metal+ PS
Dimmable	YES	YES	YES	YES
Night light	No	No	No	YES
Length	12Inch(305mm)	13.4Inch (340mm)	13.4Inch (340mm)	11.6Inch (295mm)
Width	12Inch(305mm)	13.4Inch (340mm)	13.4Inch (340mm)	11.6Inch (295mm)
Height	3.94Inch(100mm)	3.7Inch(94mm)	3.5Inch(90mm)	1.97Inch(50mm)
Environment	Damp Location	Damp Location	Damp Location	Damp Location
Certificate	ETL、FCC	ETL、FCC	ETL、FCC	ETL、FCC