

**TOPSTAR**

— Since 1958 —

# Portable EV Charger



Bluetooth



Wi-Fi



Tuya

Suitable for NA



**Features**

- OTA Remote Firmware Updates
- Enclosure Rating: NEMA Enclosure Type 4

**Application:**

- Residential Area

**Technical Data:**

	10A Max	16A Max	32A Max	40A Max
<b>Electrical Parameter</b>	Single phase input: 208-240VAC 60 Hz			
	2.4kW at 240 VAC	3.8kW at 240 VAC	7.6kW at 240 VAC	9.6kW at 240 VAC
<b>Input Cord</b>	NEMA 5-15P, NEMA 14-50 or NEMA 6-50P			
<b>Output Cable &amp; Connector</b>	18 FT/5.5 m cable (25 FT/7.5m optional)			
	SAE J1772, NACS standard compliance			
<b>Environmental Parameter</b>	Enclosure NEMA Type3			
	EV Charger NEMA Type 3R			
	Operating Temperature: -22°F to 122°F (-30°C to 50°C )			
<b>Dimension</b>	Main enclosure: 9.7 in × 4.6 in × 2.6 in ( 247 mm × 118 mm × 66 mm)			
<b>Standards</b>	NEC625, UL2594, UL 2231 compliance			
<b>Certification</b>	ETL, FCC, Energy Star Listed			

**Optional**

- Tuya
- Wi-Fi & Bluetooth
- Color customization