

**TOPSTAR**

— Since 1958 —

# LED Commercial Downlight


DUO Selectable



0-10V Dimming



5CCT Selectable



High quality aluminum frame



**Application :**

Select from Topstar's recessed downlight LED luminaires include modules/trim, ultra-slim, surface mount, LED downlights with junction box, commercial downlight, and night-light. Our luminaires are perfect choice for your new or remodel construction project with their lower energy and maintenance cost. We have products for various application, such as residential application, like living room and kitchen, and commercial application, such as school and corporate office space. Our downlight LED luminaires comes in different option, such as CCT and/or wattage selectable, standard style, 277- 347V option, and many more. Many of Topstar's downlight LED luminaires are certify for ETL, FCC, Energy Star, CA T20, T24 and CEC.

**Features :**

- 5 CCT selectable.
- 0-10V dimming.
- Compatible with most of dimmers.
- Quick and easy installation.

**Application place :**

The product is suitable for Commercial Space, Office, Hotel, Lobby, Low profile space and so on.

**Technical Date :**

|                        | LED Commercial Downlight<br>DUO Selectable |  |  |
|------------------------|--|--|--|
| Rated Voltage          | 120-277V                                   | 120-277V                                 | 120-277V                                 |
| Size                   | 6inch                                      | 8inch                                    | 10inch                                   |
| Rated Power            | 10/14/20W                                  | 12/18/25W                                | 22/28/33W                                |
| Power Factor           | 0.9  | 0.9                                      | 0.9                                      |
| Declared Luminous Flux | 1052/1474/1985lm                           | 1272/1881/2484lm                         | 2336/2992/3422lm                         |
| Color Temperature      | 5CCT(27000K/3000K/<br>3500K/4000K/5000K)   | 5CCT(27000K/3000K/<br>3500K/4000K/5000K) | 5CCT(27000K/3000K/<br>3500K/4000K/5000K) |
| Average Ra             | 90   | 90                                       | 90                                       |
| Beam Angle             | 90°  | 90°                                      | 90°                                      |
| Average Life           | 50000H                                     | 50000H                                   | 50000H                                   |
| Working Temperature    | -20°C(-4°F)~<br>40°C(+104°F)               | -20°C(-4°F)~<br>40°C(+104°F)             | -20°C(-4°F)~<br>40°C(+104°F)             |
| Material               | Aluminum + PC                              | Aluminum + PC                            | Aluminum + PC                            |
| Dimmable               | 0-10V                                      | 0-10V                                    | 0-10V                                    |
| Length                 | 8.27Inch(210mm)                            | 10.06Inch(255.5mm)                       | 11.4Inch(289.6mm)                        |

|             |                 |                    |                   |
|-------------|-----------------|--------------------|-------------------|
| Width       | 8.27Inch(210mm) | 10.06Inch(255.5mm) | 11.4Inch(289.6mm) |
| Height      | 3.78Inch(96mm)  | 4.3Inch(109.2mm)   | 4.3Inch(109.2mm)  |
| Environment | Wet Location    | Wet Location       | Wet Location      |
| Certificate | ETL、FCC、T24     | ETL、FCC、T24        | ETL、FCC、T24       |