



## FULL COLOR

With 1600 colors, customize variable light modes.



## FUNCTION SETTING

Easily arrange your plans and times.



## INSTALLATION

Mount directly to a junction box, or retrofit into a wide range of existing cans



**Application:**

Convert your old recessed downlights to advanced LED energy-saving technology with the smart downlight from TOPSTAR. This innovative recessed downlight comes with a tethered J-Box and built-in trim for hardwire installation directly into finished ceilings without recessed cans. Use your favorite smart device to easily turn lights on/off, dim, set groups and schedules from anywhere. Choose energizing daylight or wind down with relaxing soft white light. Get creative with color, it's all up to you. Control lighting with simple voice commands or an intuitive mobile app. Setup is simple: the downlights come with quick-connect wiring and a medium base adapter. Install and connect directly to your 2.4GHz home Wi-Fi in minutes. Enhance high-CRI LED light makes colors vibrant and skin tones look more natural, all while saving energy and lasting for years. It has never been easier to customize your home's lighting to suit your lifestyle.

**Feature & Benefits:**

1. Function optional: DIM, TW, RGBCW.
2. Support Matter over Wi-Fi or Matter over Thread protocol.
3. With the ability to support a stunning array of 1600 colors and an adjustable color temperature ranging from 2700K to 6500K.
4. Enhance high-CRI LED light makes colors vibrant.
5. Turn on/off, adjust lighting, set groups and schedules with your smartphone.
6. Compatible with Google Home and Amazon Alexa voice assistants.
7. Converts conventional recessed lighting to energy saving smart LED technology.

**Application place:**

The product is suitable for residential home, living room and so on.



**Technical Data:**

	TSZ10DL--LD0**	TSZ13DL--LD0**
<b>Lamp Type</b>	4Inch Downlight	6Inch Downlight
<b>Rated Voltage</b>	120V	
<b>Rated Power</b>	10W	13W
<b>Power Factor</b>	0.7	
<b>Declared Luminous Flux</b>	800lm	1050lm
<b>Color Temperature</b>	2700~6500K & RGB	
<b>Average Ra</b>	90	
<b>Beam Angle</b>	110°	
<b>Average Life</b>	25000H	
<b>Working Temperature</b>	-20℃(-4℉)~40℃(+104℉)	
<b>Material</b>	Metal + Plastic	
<b>Dimmable</b>	App Control	
<b>Diameter</b>	4.92Inch(125mm)	6.89Inch(175mm)
<b>Height</b>	1.26Inch(32mm)	1.26Inch(32mm)
<b>Base</b>	E26	
<b>Environment</b>	Damp Location	
<b>Certificate</b>	ETL、FCC、CEC-T20	