

TOPSTAR

— Since 1958 —

Smart Slim Panel Downlight



FULL COLOR

With 1600 colors, customize variable light modes.



FUNCTION SETTING

Easily arrange your plans and times.



FLUSH MOUNTING

Slim and recessed options available, both with beautiful aesthetics



Application:

Convert your old recessed downlights to advanced LED energy-saving technology with the smart downlight from TOPSTAR. This innovative recessed downlight comes with a tethered J-Box and built-in trim for hardwire installation directly into finished ceilings without recessed cans. Use your favorite smart device to easily turn lights on/off, dim, set groups and schedules from anywhere. Choose energizing daylight or wind down with relaxing soft white light. Get creative with color, it's all up to you. Control lighting with simple voice commands or an intuitive mobile app. Setup is simple: the downlights come with quick-connect wiring and a medium base adapter. Install and connect directly to your 2.4GHz home Wi-Fi in minutes. Enhance high-CRI LED light makes colors vibrant and skin tones look more natural, all while saving energy and lasting for years. It has never been easier to customize your home's lighting to suit your lifestyle.

Feature & Benefits:

- 1.Function optional: DIM, TW, RGBCW.
- 2.Support Matter over Wi-Fi or Matter over Thread protocol.
- 3.With the ability to support a stunning array of 1600 colors and an adjustable color temperature ranging from 2700K to 6500K.
- 4.Enhance high-CRI LED light makes colors vibrant.
- 5.Turn on/off, adjust lighting, set groups and schedules with your smartphone.
- 6.Compatible with Google Home and Amazon Alexa voice assistants.
- 7.Converts conventional recessed lighting to energy saving smart LED technology

Application place:

The product is suitable for residential home, living room and so on.



Technical Data:

	TSZ10DL--LD0**	TSZ13DL--LD0**
Lamp Type	4Inch Downlight	6Inch Downlight
Rated Voltage	120V	120V
Rated Power	10W	13W
Power Factor	0.7	0.7
Declared Luminous Flux	700lm	1000lm
Color Temperature	2700~6500K & RGB	2700~6500K & RGB
Average Ra	90	90
Beam Angle	110°	110°
Average Life	25000H	25000H
Working Temperature	-20°C(-4°F)~40°C(+104°F)	-20°C(-4°F)~40°C(+104°F)
Material	Metal + Plastic	Metal + Plastic
Dimmable	App Control	App Control
Diameter	4.92Inch(125mm)	6.89Inch(175mm)
Height	0.71Inch(18mm)	0.71Inch(18mm)
Base	E26	E26
Environment	Damp Location	Damp Location
Certificate	ETL、FCC、CEC-T20	ETL、FCC、CEC-T20