

PAR Lamp - 3CCT







GLOWING EFFECT

Instant on to full brightness and luminance uniformity



POLLUTION FREE

RoHS compliant and are 100% mercury free



COLOR SELECT TECHNOLOGY

Adjustable: 3000&3500&5000K



DIMMABLE

TRIAC Dimming









Introduce:

The TOPSTAR LED PAR reflector light features our highest quality and most energy efficient light. It has a high (CRI) of 90+ so colors appear more vivid and natural. Rated to last an average life of 25,000 Hours, the bulb lasts up to 25 times longer than the equivalent incandescent light and is much more energy efficient saving you time and money. Preset the color temperature with a toggle on the PAR LED bright for your need. Get instant on to full brightness with relatively cool running performance. The high performance versatile PAR LED bright white light is fully dimmable and suitable for indoor and outdoor use making it an ideal replacement light for outdoor security lighting, recess and track lighting applications.

Features & Benefits:

- Instant on to full brightness and TRIAC dimmable
- 3 color temperatures optional, let you choose your favorite color temperature
- Enhance high-CRI LED light makes colors vibrant
- These LED lights do not contain mercury and won't release any hazardous gases into the air
- With a lifetime of up to 25,000 hours, you can reduce the hassle of frequently replacing your light bulbs
- Energy efficient LED technology uses considerably less power and last longer compared to equivalent incandescent lights

Application place:

The product is suitable for courtyard, corridor, living room and so on.

Available Sizes:



Туре	Diameter Height		
TSZ7PAR20-LD00*	2.60 Inch(66mm)	3.38 Inch(86mm)	
TSZ9.5PAR30-LD00*	3.37 Inch(96mm)	3.58 Inch(91mm)	
TSZ9.5P30-LD	3.37 Inch(96mm)	4.72 Inch(120mm)	
TSZ13PAR38-LD00*	4.84 Inch(123mm)	5.23 Inch(133mm)	
TSZ14P38-LD	4.84 Inch(123mm)	5.23 Inch(133mm)	



Technical Date:

	TSZ7PAR20 -LD00*	TSZ9.5PAR30 -LD00*	TSZ9.5P30 -LD	TSZ13PAR38 -LD00*	TSZ14P38 -LD
Lamp Type	PAR20	PAR30	PAR30-L	PAR38	PAR38
Rated Voltage	120V				
Rated Power	7W	9.5W	9.5W	13W	14W
Incandescent Equivalent	50W	75W	75W	90W	120W
Power Factor	0.7				
Declared Luminous Flux	450lm	850lm	850lm	110lm	1200lm
СВСР	714cd	1640cd	1640cd	1533cd	2231cd
Color Temperature	3000&3500&5000K				
Average Ra	Ra90				
Beam Angle	35°	35°	35°	40°	40°
Average Life	25000H				
Working Temperature	-20°(-4°F)~40°C(+104°F)				
Material	Plastic				
Dimmable	YES				
Weight	0.110Lb (50g)	0.198Lb (90g)	0.220Lb (100g)	0.331Lb (150g)	0.331Lb (150g)
Base	E26				
Environment	Wet Location				
Certificate	ETL、FCC、CEC-T20				