

# **BR Lamp - 5CCT**







#### **GLOWING EFFECT**

Instant on to full brightness and luminance uniformity



## **POLLUTION FREE**

RoHS compliant and are 100% mercury free



## **COLOR SELECT TECHNOLOGY**

Adjustable: 2700&3000&3500&4000&5000K



**DIMMABLE TRIAC Dimming** 









#### Introduce:

Enjoy all the benefits of advanced LED energy-saving technology with the TOPSTAR LED BR Lamp. The light bulbs feature high color rendering index light with superior light quality and rich vivid color. This LED BR Lamp replaces incandescent bulb, producing a similar light output using less electricity. Preset the color temperature with a toggle on the bulb for your need. Get instant on to full brightness with relatively cool running performance. These TOPSTAR LED BR Lamp have an average life of 15,000 hours are RoHS compliant, and are 100% mercury free. Choose a dependable Title 20 Compliant bulb for general purpose residential or commercial applications.


#### Features & Benefits:

- Instant on to full brightness and TRIAC dimmable
- 5 color temperatures optional, let you choose your favorite color temperature.
- Enhance high-CRI LED light makes colors vibrant
- These LED lights do not contain mercury and won't release any hazardous gases into the air
- With a lifetime of up to 15,000 hours, you can reduce the hassle of frequently replacing your light bulbs
- Energy efficient LED technology uses considerably less power and last longer compared to equivalent incandescent lights

# Application place:

The product is suitable for residential home, living room and so on.

#### Available Sizes:



Туре	Diameter	Height
TSZ8BR30-LD003	3.70 Inch(94mm)	5.04lnch(128mm)
TSZ8BR30-LD00*	3.70 Inch(94mm)	5.04Inch(128mm)



## **Technical Date:**

	TSZ8BR30-LD003	TSZ8BR30-LD00*
Lamp Type	BR30	
Rated Voltage	120V	
Rated Power	8W	
Incandescent Equivalent	65W	75W
Power Factor	0.7	
Declared Luminous Flux	650lm	800lm
СВСР	4310&1220cd	5414&1533cd
Color Temperature	2700&3000&3500&4000&5000K	
Average Ra	Ra90	
Beam Angle	110°	
Average Life	15000H	
Working Temperature	-20°(-4°F)~40°C(+104°F)	
Material	Plastic	
Dimmable	YES	
Weight	0.243Lb(110g)	
Base	E26	
Environment	Damp Location	
Certificate	ETL、FCC、CEC-T20	